



HORIUCHI MACHINE (Thailand) CO., LTD. บริษัท โฮริอุจิ แมชชีน (ประเทศไทย) จำกัด

12/23 Moo5, RachaThawa, BangPlee, Samutprakarn. 10540 Thailand.
 12/23 หมู่ 5 ซอยกิ่งแก้ว 44 ตำบลราชาเทวะ อำเภอบางพลี จังหวัดสมุทรปราการ 10540
 TEL: +66-86-305-5147 FAX: +66-2-736-8822
<http://www.hmt.co.th/> Email:info@hmt.co.th

HITACHI ZOSEN. LTD. Production 600 Ton Single Action Crankless Press

Performance Specification	
Model designation	S4-600-400-215 Four(4)Point Suspension Press
Max. Capacity	600 ton
Capacity Limitation	15 mm
Stroke of Slide	750 mm
Slide Adjustment	400 mm
Die Height(Max)	1820 mm (Stroke Down – Slide Adjust Up)
Bolster Size	4000 x 2150 mm (RL x FB)
Bottom Size of Slide	4000 x 2150 mm (RL x FB)
Strokes Per Minute	12 & 16 spm. (Working Strokes: 10 - 12 spm)
Die Cushion Type	Pneumatic & Oil Hydraulic Control/1 Pad 1cylinder
Capacity of Die Cushion	150 ton
Die Cushion Pad Size	---
Stroke of Die Cushion	300 mm
Die Cushion Locking Device	Attached
	Attached
Main Motor Capacity	75 Kw 440V 60Hz
Bolster Type	Right side Cross Type Moving Bolster (2PC)

Year of manufacture:1969 Year

